

GiK API

API and SDK Documentation

Version: 1

Welcome to the GiK API reference, which lets you easily create a bot and conversations.

The GiK API is organized around the REST methodology. It uses resource-oriented URLs, and common HTTP response codes to indicate API errors.

All requests are authenticated using an `api-key` which can be obtained from your ApiKeys (<https://getgik.com/apikey/index>).

Pdf ([logic/docs/GiKAPI.pdf](#))

Openapi ([logic/docs/openapi.json](#))

Postman ([logic/docs/postman.json](#))

Bots

listBotsDev

List of Bots

List of Bots with criteria

GET

/v1/bots

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X GET \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
"https://getgik.com/v1/bots?page=56&limit=56&keyword=keyword_example"
```

Scopes

Parameters

Query parameters

Name	Description
page	Integer <i>Page to show (default: 1)</i>
limit	Integer <i>Amount of results (default: 10; maximum: 100)</i>
keyword	String <i>Search name of the Bot</i>

Responses

Status: 200 - List of bot objects

Schema

```
▼ { []  
  conversations: ▼ [ []  
    ▼ { []  
      bot_id:      integer  
      name:       string  
      description: string  
      status_id:   integer  
      creation_date: string  
    ]  
  pagination: ▼ { []  
    has_next:     boolean  
    has_previous: boolean  
    next_page:    integer  
    pages:        integer  
    previous_page: integer  
    total:        integer
```

Status: 400 - An error message when listing bots. Limit must be less than 100

Schema

```
▼ { []  
  statusCode:  integer  
  errorMessage: string
```

Status: 404 - An error message when listing bots.

Schema

```
▼ { []  
  statusCode:  integer  
  errorMessage: string
```

Conversations

createConversationDev

Create Conversation

Creates a conversation for specific bot

POST

Usage and SDK Samples

[Curl](#) [Java](#) [Android](#) [Obj-C](#) [JavaScript](#) [C#](#) [PHP](#) [Perl](#) [Python](#) [Rust](#)

```
curl -X POST \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
"https://getgik.com/v1/conversations" \
-d '{
  "name" : "name",
  "bot_id" : 0
}'
```

Scopes

Parameters

Body parameters

Name	Description
createConversation	A Conversation request information object ▼ { [] Required: bot_id,name name: string bot_id: integer

Responses

Status: 200 - A conversation object

[Schema](#)

```
▼ { []  

  id: integer  

  name: string  

  bot_id: integer  

  creation_date: string
```

Status: 404 - An error message when creating a new conversation. Conversation name exists

[Schema](#)

```
▼ { []  

  statusCode: integer  

  errorMessage: string
```

deleteConversationDev

Delete Conversation

Deletes a conversation already created

DELETE

/v1/conversations/{id}

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X DELETE \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
"https://getgik.com/v1/conversations/{id}"
```

Scopes

Parameters

Path parameters

Name	Description
id*	<p>Integer <i>The conversation id parameter to delete</i></p> <p>Required</p>

Responses

Status: 200 - A Message object. Conversation deleted successfully

Schema

```
▼ { []
  message: string
```

Status: 404 - An error message when deleting a conversation. Conversation not Found

Schema

```
▼ { []
  statusCode: integer
  errorMessage: string
```

getConversationDev

Get a Conversation

Creates a conversation for specific bot

GET

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X GET \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
"https://getgik.com/v1/conversations/{id}"
```

Scopes

Parameters

Path parameters

Name	Description
id*	<p>Integer <i>The conversation id parameter</i> Required</p>

Responses

Status: 200 - A conversation object

Schema

```
▼ { [] }
  id:      integer
  name:    string
  bot_id:   integer
  creation_date: string
```

Status: 404 - An error message when getting a conversation. Conversation not Found

Schema

```
▼ { [] }
  statusCode:  integer
  errorMessage: string
```

listConversationsDev

List Conversations

List conversations with criteria

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X GET \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
"https://getgik.com/v1/conversations?page=56&limit=56&keyword=keyword_example"
```

Scopes

Parameters

Query parameters

Name	Description
page	Integer <i>Page to show (default: 1)</i>
limit	Integer <i>Amount of results (default: 10; maximum: 100)</i>
keyword	String <i>Search name of the Conversations</i>

Responses

Status: 200 - List of conversation objects

Schema

```
▼ { []
  conversations: ▼ [ ]
    ▼ { []
      id:           integer
      name:         string
      bot_id:       integer
      creation_date: string
    ]
  pagination:   ▼ { []
    has_next:     boolean
    has_previous: boolean
    next_page:    integer
    pages:        integer
    previous_page: integer
    total:        integer
  }
}
```

Status: 400 - An error message when listing conversations. Limit must be less than 100

Schema

```
▼ { []
  statusCode:  integer
}
```

```
errorMessage: string
```

Status: 404 - An error message when listing conversations.

Schema

```
▼ { []
  statusCode: integer
  errorMessage: string
```

updateConversationDev

Update Conversation Info

Update a conversation name or/and bot

PUT

```
/v1/conversations/{id}
```

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X PUT \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
"https://getgik.com/v1/conversations/{id}" \
-d '{
  "name" : "name",
  "bot_id" : 0
}'
```

Scopes

Parameters

Path parameters

Name	Description
id*	<p>Integer <i>The conversation id parameter</i></p> <p>Required</p>

Body parameters

Name	Description
------	-------------

createConversation	A Conversation request information object ▼ { [] Required: bot_id,name name: string bot_id: integer
--------------------	---

Responses

Status: 200 - A conversation object

Schema

```
▼ { []  
  id: integer  
  name: string  
  bot_id: integer  
  creation_date: string
```

Status: 404 - An error message when updating a conversation. Conversation name exists

Schema

```
▼ { []  
  statusCode: integer  
  errorMessage: string
```

Messages

listMessagesDev

List of Messages

List of Messages with criteria

GET

/v1/messages

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X GET \  
-H "Authorization: Bearer [[accessToken]]" \  
-H "Accept: application/json" \  
"https://getgik.com/v1/messages?page=56&limit=56&keyword=keyword_example&conversation_id=56"
```

Scopes

Parameters

Query parameters

Name	Description
page	Integer <i>Page to show (default: 1)</i>
limit	Integer <i>Amount of results (default: 10; maximum: 100)</i>
keyword	String <i>Search text of the Message</i>
conversation_id	Integer <i>id of the conversation that message belongs</i>

Responses

Status: 200 - List of messages that matches the criteria

Schema

```
▼ { []  
  messages: ▼ [ []  
    ▼ { []  
      message_id:     integer  
      text:          string  
      conversation_id: string  
      bot_id:         integer  
      type_id:        string  
      page_ids:       integer  
      intention:      string  
      file_name:      string  
      total_cost:     integer  
      num_tokens:     integer  
      creation_date:  string  
    ]  
  pagination: ▼ { []  
    has_next:       boolean  
    has_previous:   boolean  
    next_page:      integer  
    pages:          integer  
    previous_page:  integer  
    total:          integer
```

Status: 400 - An error message when listing messages. Limit must be less than 100

Schema

```
▼ { []
  statusCode: integer
  errorMessage: string
```

Status: 404 - An error message when listing messages.

Schema

```
▼ { []
  statusCode: integer
  errorMessage: string
```

sendMessageDev

Process a message for a Conversation

Creates a message request for a message response

POST

/v1/messages

Usage and SDK Samples

Curl Java Android Obj-C JavaScript C# PHP Perl Python Rust

```
curl -X POST \
-H "Authorization: Bearer [[accessToken]]" \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
"https://getgik.com/v1/messages" \
-d '{
  "conversation_id" : "conversation_id",
  "text" : "text"
}'
```

Scopes

Parameters

Body parameters

Name	Description
messageRequest	A Message process request object ▼ { [] Required: conversation_id,text text: string conversation_id: string

Responses

Status: 200 - A Message object with response

Schema

```
▼ { []  
  message_id: integer  
  text: string  
  conversation_id: string  
  bot_id: integer  
  type_id: string  
  page_ids: integer  
  intention: string  
  file_name: string  
  total_cost: integer  
  num_tokens: integer  
  creation_date: string
```

Status: 402 - An error message when processing a message. Query Limit Reached

Schema

```
▼ { []  
  text: string
```

Status: 404 - An error message when processing a message. Conversation not found

Schema

```
▼ { []  
  statusCode: integer  
  errorMessage: string
```

Suggestions, contact, support and error reporting;

Information URL: <https://getgik.com> (<https://getgik.com>)

Contact Info: info@cari.ai.com (info@cari.ai.com)

All rights reserved

<http://apache.org/licenses/LICENSE-2.0.html>